



UL-certified products are highlighted in grey



31 252


Class CC cylindrical fuses

**Class CC fuse
time delay
complies with UL 248-4**

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Pack size	Weight kg/100 units	Part no.
Class CC (10 x 38) time delay	0.5A	600V AC	200kA	10	0.8	31 394
	1.0A	600V AC	200kA	10	0.8	31 244
	1.5A	600V AC	200kA	10	0.8	31 395
	2.0A	600V AC	200kA	10	0.8	31 245
	2.5A	600V AC	200kA	10	0.8	31 396
	3.0A	600V AC	200kA	10	0.8	31 397
	4.0A	600V AC	200kA	10	0.8	31 246
	5.0A	600V AC	200kA	10	0.8	31 398
	6.0A	600V AC	200kA	10	0.8	31 247
	8.0A	600V AC	200kA	10	0.8	31 399
	10.0A	600V AC	200kA	10	0.8	31 248
	12.0A	600V AC	200kA	10	0.8	31 400
	15.0A	600V AC	200kA	10	0.8	31 249
	20.0A	600V AC	200kA	10	0.8	31 250
25.0A	600V AC	200kA	10	0.8	31 251	
30.0A	600V AC	200kA	10	0.8	31 252	



UL-certified products are highlighted in grey



31 241

Class CC cylindrical fuses

**Class CC fuse
fast acting
complies with UL 248-4**

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Pack size	Weight kg/100 units	Part no.
Class CC (10 x 38) fast acting	0.5A	600V AC	200kA	10	0.8	31 401
	1.0A	600V AC	200kA	10	0.8	31 235
	1.5A	600V AC	200kA	10	0.8	31 402
	2.0A	600V AC	200kA	10	0.8	31 236
	2.5A	600V AC	200kA	10	0.8	31 403
	3.0A	600V AC	200kA	10	0.8	31 404
	4.0A	600V AC	200kA	10	0.8	31 237
	5.0A	600V AC	200kA	10	0.8	31 405
	6.0A	600V AC	200kA	10	0.8	31 238
	8.0A	600V AC	200kA	10	0.8	31 406
	10.0A	600V AC	200kA	10	0.8	31 239
	12.0A	600V AC	200kA	10	0.8	31 407
	15.0A	600V AC	200kA	10	0.8	31 240
	20.0A	600V AC	200kA	10	0.8	31 241
25.0A	600V AC	200kA	10	0.8	31 242	
30.0A	600V AC	200kA	10	0.8	31 243	



UL-certified products are highlighted in grey

31 353	31 363	03 231	03 236
--------	--------	--------	--------

Class J cylindrical fuses

**Class J fuse
time delay
complies with UL 248-8**

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Pack size	Weight kg/100 units	Part no.
Class J (21 x 57) time delay	1A	600V AC	200kA	10	4.4	31 333
	2A	600V AC	200kA	10	4.4	31 338
	3A	600V AC	200kA	10	4.4	31 342
	4A	600V AC	200kA	10	4.4	31 345
	5A	600V AC	200kA	10	4.4	31 347
	6A	600V AC	200kA	10	4.4	31 349
	8A	600V AC	200kA	10	4.4	31 351
	9A	600V AC	200kA	10	4.4	31 352
	10A	600V AC	200kA	10	4.4	31 353
	12A	600V AC	200kA	10	4.4	31 354
	15A	600V AC	200kA	10	4.4	31 355
	20A	600V AC	200kA	10	4.4	31 357
25A	600V AC	200kA	10	4.4	31 358	
30A	600V AC	200kA	10	4.4	31 359	
Class J (27 x 60) time delay	35A	600V AC	200kA	10	7.6	31 360
	40A	600V AC	200kA	10	7.6	31 361
	45A	600V AC	200kA	10	7.6	31 362
	50A	600V AC	200kA	10	7.6	31 363
	60A	600V AC	200kA	10	7.6	31 364
Class J (29 x 117) time delay	70A	600V AC	200kA	1	15.4	03 228
	80A	600V AC	200kA	1	15.4	03 229
	90A	600V AC	200kA	1	15.4	03 230
	100A	600V AC	200kA	1	15.4	03 231
Class J (41 x 146) time delay	110A	600V AC	200kA	1	38.2	03 232
	125A	600V AC	200kA	1	38.2	03 233
	150A	600V AC	200kA	1	38.2	03 234
	175A	600V AC	200kA	1	38.2	03 235
	200A	600V AC	200kA	1	38.2	03 236
Class J (54 x 181) time delay	225A	600V AC	200kA	1	76.0	03 237
	250A	600V AC	200kA	1	76.0	03 238
	300A	600V AC	200kA	1	76.0	03 239
	350A	600V AC	200kA	1	76.0	03 240
	400A	600V AC	200kA	1	76.0	03 241



UL-certified products are highlighted in grey



31 323	31 514	03 215	03 220
--------	--------	--------	--------

Class J cylindrical fuses

Class J fuse fast acting complies with UL 248-8

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Pack size	Weight kg/100 units	Part no.	
Class J (21 x 57) fast acting	1A	600V AC	200kA	10	4.4	31 320	16
	2A	600V AC	200kA	10	4.4	31 328	16
	3A	600V AC	200kA	10	4.4	31 321	16
	4A	600V AC	200kA	10	4.4	31 329	16
	5A	600V AC	200kA	10	4.4	31 330	16
	6A	600V AC	200kA	10	4.4	31 322	16
	8A	600V AC	200kA	10	4.4	31 331	16
	10A	600V AC	200kA	10	4.4	31 323	16
	12A	600V AC	200kA	10	4.4	31 332	16
	15A	600V AC	200kA	10	4.4	31 324	16
	20A	600V AC	200kA	10	4.4	31 325	16
	25A	600V AC	200kA	10	4.4	31 326	16
30A	600V AC	200kA	10	4.4	31 327	16	
Class J (27 x 60) fast acting	35A	600V AC	200kA	10	7.6	31 511	16
	40A	600V AC	200kA	10	7.6	31 512	16
	45A	600V AC	200kA	10	7.6	31 513	16
	50A	600V AC	200kA	10	7.6	31 514	16
	60A	600V AC	200kA	10	7.6	31 515	16
Class J (29 x 117) fast acting	70A	600V AC	200kA	1	15.4	03 214	16
	80A	600V AC	200kA	1	15.4	03 215	16
	90A	600V AC	200kA	1	15.4	03 216	16
	100A	600V AC	200kA	1	15.4	03 217	16
Class J (41 x 146) fast acting	110A	600V AC	200kA	1	38.2	03 218	16
	125A	600V AC	200kA	1	38.2	03 219	16
	150A	600V AC	200kA	1	38.2	03 220	16
	175A	600V AC	200kA	1	38.2	03 221	16
	200A	600V AC	200kA	1	38.2	03 222	16
Class J (54 x 181) fast acting	225A	600V AC	200kA	1	76.0	03 223	16
	250A	600V AC	200kA	1	76.0	03 224	16
	300A	600V AC	200kA	1	76.0	03 225	16
	350A	600V AC	200kA	1	76.0	03 226	16
	400A	600V AC	200kA	1	76.0	03 227	16

Designation for UL 508A	Accessories	2 27 510	→

Wohner_Accessories_Cylindrical_Fuses_Class-CC-J_en_1211.pdf



www.klinkmann.com

Helsinki
tel. +358 9 540 4940
automation@klinkmann.fi

Yekaterinburg
tel. +7 343 376 5393
yekaterinburg@klinkmann.spb.ru

Vilnius
tel. +370 5 215 1646
post@klinkmann.lt

St. Petersburg
tel. +7 812 327 3752
samara@klinkmann.spb.ru

Samara
tel. +7 846 273 95 85
samara@klinkmann.spb.ru

Tallinn
tel. +372 668 4500
klinkmann.est@klinkmann.ee

Moscow
tel. +7 495 641 1616
moscow@klinkmann.spb.ru

Kiev
tel. +38 044 495 33 40
klinkmann@klinkmann.kiev.ua

Minsk
tel. +375 17 200 0876
minsk@klinkmann.com

Riga
tel. +371 6738 1617
klinkmann@klinkmann.lv