



31 185

gG cylindrical fuses

gG (gL) fuses complies with IEC 60269-2

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Power output	Pack size	Weight kg/100 units	Part no.	
8 x 31 (gG)	4A	400V AC	20kA		10	0.1	31 177	17
	6A	400V AC	20kA		10	0.1	31 178	17
	10A	400V AC	20kA		10	0.1	31 179	17
	16A	400V AC	20kA		10	0.1	31 180	17
	20A	400V AC	20kA		10	0.1	31 181	17
10 x 38 (gG)	1A	500V AC	120kA	0.5W	10	0.6	31 008	17
	2A	500V AC	120kA	0.6W	10	0.6	31 182	17
	4A	500V AC	120kA	0.7W	10	0.6	31 183	17
	6A	500V AC	120kA	0.8W	10	0.6	31 184	17
	8A	500V AC	120kA	0.9W	10	0.6	31 009	17
	10A	500V AC	120kA	1.0W	10	0.6	31 185	17
	12A	500V AC	120kA	1.3W	10	0.6	31 010	17
	16A	500V AC	120kA	1.6W	10	0.6	31 186	17
	20A	500V AC	120kA	2.0W	10	0.6	31 187	17
	25A	500V AC	120kA	2.6W	10	0.6	31 188	17
14 x 51 (gG)	2A	690V AC	80kA	0.8W	10	1.9	31 011	17
	6A	690V AC	80kA	1.0W	10	1.9	31 017	17
	10A	690V AC	80kA	1.3W	10	1.9	31 190	17
	16A	690V AC	80kA	2.0W	10	1.9	31 191	17
	20A	690V AC	80kA	2.5W	10	1.9	31 192	17
	25A	690V AC	80kA	3.3W	10	1.9	31 193	17
	32A	500V AC	80kA	3.5W	10	1.9	31 194	17
	40A	500V AC	120kA	4.8W	10	1.9	31 195	17
22 x 58 (gG)	16A	690V AC	80kA	2.3W	10	5.0	31 018	17
	20A	690V AC	80kA	2.8W	10	5.0	31 019	17
	25A	690V AC	80kA	3.6W	10	5.0	31 197	17
	32A	690V AC	80kA	3.7W	10	5.0	31 198	17
	40A	690V AC	80kA	4.5W	10	5.0	31 199	17
	50A	690V AC	80kA	5.2W	10	5.0	31 200	17
	63A	500V AC	80kA	6.9W	10	5.0	31 201	17
	80A	500V AC	120kA	7.8W	10	5.0	31 202	17
	100A	500V AC	120kA	8.6W	10	5.0	31 203	17
	125A	400V AC	120kA	11.4W	10	5.0	31 204	17



31 366

gG cylindrical fuses

**gG (gL) fuses, with striker
complies with IEC 60269-2**

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Power output	Pack size	Weight kg/100 units	Part no.	
14 x 51 (gG)	2A	500V AC	80kA	0.9W	10	2.0	31 393	17
	4A	500V AC	80kA	1.0W	10	2.0	31 365	17
	6A	500V AC	80kA	1.1W	10	2.0	31 366	17
	8A	500V AC	80kA	1.2W	10	2.0	31 367	17
	10A	500V AC	80kA	1.3W	10	2.0	31 368	17
	12A	500V AC	80kA	1.7W	10	2.0	31 369	17
	16A	500V AC	80kA	2.0W	10	2.0	31 370	17
	20A	500V AC	80kA	2.5W	10	2.0	31 371	17
	25A	500V AC	80kA	3.3W	10	2.0	31 372	17
	32A	500V AC	120kA	3.5W	10	2.0	31 373	17
	40A	500V AC	120kA	4.8W	10	2.0	31 374	17
22 x 58 (gG)	50A	400V AC	120kA	4.9W	10	2.0	31 375	17
	6A	690V AC	80kA	1.2W	10	5.2	31 376	17
	8A	690V AC	80kA	1.3W	10	5.2	31 377	17
	10A	690V AC	80kA	1.4W	10	5.2	31 378	17
	12A	690V AC	80kA	1.8W	10	5.2	31 379	17
	16A	690V AC	80kA	2.1W	10	5.2	31 380	17
	20A	690V AC	80kA	2.7W	10	5.2	31 381	17
	25A	690V AC	80kA	3.6W	10	5.2	31 382	17
	32A	690V AC	80kA	3.7W	10	5.2	31 383	17
	40A	690V AC	80kA	4.5W	10	5.2	31 384	17
	50A	690V AC	80kA	5.2W	10	5.2	31 385	17
	63A	500 V AC	80kA	6.9W	10	5.2	31 386	17
	80A	500V AC	80kA	7.8W	10	5.2	31 387	17
100A	500V AC	120kA	8.6W	10	5.2	31 388	17	
125A	400V AC	120kA	11.4W	10	5.2	31 389	17	



UL-certified products are highlighted in grey



31 209

gR cylindrical fuses

gR fuses
complies with IEC/EN 60269-4

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Power output	Pack size	Weight kg/100 units	Part no.	
10 x 38 (gR)	1A	660V AC	200kA	0.9W	10	0.6	31 205	17
	2A	660V AC	200kA	1.0W	10	0.6	31 206	17
	4A	660V AC	200kA	1.1W	10	0.6	31 207	17
	6A	660V AC	200kA	1.6W	10	0.6	31 208	17
	10A	660V AC	200kA	2.1W	10	0.6	31 209	17
	12A	660V AC	200kA	3.1W	10	0.6	31 210	17
	16A	660V AC	200kA	4.4W	10	0.6	31 211	17
	20A	660V AC	200kA	5.8W	10	0.6	31 212	17
	25A	660V AC	200kA	6.8W	10	0.6	31 213	17
14 x 51 (gR)	30A	660V AC	200kA	8.2W	10	0.6	31 214	17
	10A	690V AC	200kA	2.6W	10	1.9	31 215	17
	16A	690V AC	200kA	4.7W	10	1.9	31 216	17
	20A	690V AC	200kA	6.0W	10	1.9	31 217	17
	25A	690V AC	200kA	7.6W	10	1.9	31 218	17
	32A	690V AC	200kA	9.5W	10	1.9	31 219	17
	40A	690V AC	200kA	10.0W	10	1.9	31 220	17
22 x 58 (gR)	50A	690V AC	200kA	12.0W	10	1.9	31 221	17
	20A	690V AC	200kA	6.0W	10	5.0	31 222	17
	25A	690V AC	200kA	7.2W	10	5.0	31 223	17
	32A	690V AC	200kA	9.6W	10	5.0	31 224	17
	40A	690V AC	200kA	12.0W	10	5.0	31 225	17
	50A	690V AC	200kA	15.0W	10	5.0	31 226	17
	63A	690V AC	200kA	16.0W	10	5.0	31 227	17
	80A	690V AC	200kA	18.0W	10	5.0	31 228	17
100A	690V AC	200kA	19.0W	10	5.0	31 229	17	

Designation for UL 508A			



31 544

31 558

gPV cylindrical fuses

Use of gPV fuses, as per IEC/EN 60269-6 for photovoltaic applications

Size	Rated current	Rated voltage	Rated short circuit breaking capacity	Power output	Pack size	Weight kg/100 units	Part no.	
10 x 38 (gPV)	10A	1000V DC	30kA / 1000V DC	1.5W	10	0.6	31 544	17
	12A	1000V DC	30kA / 1000V DC	1.6W	10	0.6	31 545	17
	16A	1000V DC	30kA / 1000V DC	2.1W	10	0.6	31 546	17
	20A	1000V DC	30kA / 1000V DC	2.5W	10	0.6	31 547	17
14 x 85 (gPV)	16A	1100V DC	30kA / 1100V DC	3.8W	10	2.7	31 560	17
	20A	1100V DC	30kA / 1100V DC	4.7W	10	2.7	31 559	17
	25A	1000V DC	30kA / 1000V DC	5.9W	10	2.7	31 558	17
delivery date on request								

Wohner_Accessories_Cylindrical_Fuses_en_1211.pdf

KLINKMANN
www.klinkmann.com

Helsinki
tel. +358 9 540 4940
automation@klinkmann.fi

St. Petersburg
tel. +7 812 327 3752
klinkmann@klinkmann.spb.ru

Moscow
tel. +7 495 641 1616
moscow@klinkmann.spb.ru

Yekaterinburg
tel. +7 343 376 5393
yekaterinburg@klinkmann.spb.ru

Samara
tel. +7 846 273 95 85
samara@klinkmann.spb.ru

Kiev
tel. +38 044 495 33 40
klinkmann@klinkmann.kiev.ua

Riga
tel. +371 6738 1617
klinkmann@klinkmann.lv

Vilnius
tel. +370 5 215 1646
post@klinkmann.lt

Tallinn
tel. +372 668 4500
klinkmann.est@klinkmann.ee

Minsk
tel. +375 17 200 0876
minsk@klinkmann.com