

12.1-inch Standard Model

GP-4601T / GP-4603T

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | | | | |
|--------------------------------|----------------------------------------------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------|------------------------------|
| Model # | AC: PFXGP4601TAA DC: PFXGP4601TAD | AC: PFXGP4601TAAC DC: PFXGP4601TADC | AC: PFXGP4601TMA DC: PFXGP4601TMD | DC: PFXGP4603TAD |
| Coating Model | NO | YES | NO | - |
| Isolated | - | - | - | YES |
| Touch Panel Type | Analog Resistive Touch Panel | | Matrix Resistive Touch Panel | Analog Resistive Touch Panel |
| Display | 65,536 color TFT、LED Backlight、 16-level Brightness Adjustment、SVGA 800x 600 | | | |
| Memory | FLASH EPROM 32M byte (internal memory), SRAM 512K byte (backup memory) | | | |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 | | | |
| Operation Temperature | 0 to 55°C [32 to 131°F] | | | |
| Alarm Analysis Function | Supported | | | |

10.4-inch Standard Model

GP-4501T / GP-4503T

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | | | | |
|-------------------------|--------------------------------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------|------------------------------|
| Model # | AC: PFXGP4501TAA DC: PFXGP4501TAD | AC: PFXGP4501TAAC DC: PFXGP4501TADC | AC: PFXGP4501TMA DC: PFXGP4501TMD | DC: PFXGP4503TAD |
| Coating Model | NO | YES | NO | - |
| Isolated | - | - | - | YES |
| Touch Panel Type | Analog Resistive Touch Panel | | Matrix Resistive Touch Panel | Analog Resistive Touch Panel |
| Display | 65,536 color TFT、LED Backlight、 16-level Brightness Adjustment、VGA 640x 480 | | | |
| Memory | FLASH EPROM 32M byte (internal memory), | | | |

| | |
|--------------------------------|-------------------------------------------------------------------------------------------|
| | SRAM 512K byte (backup memory) |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 |
| Operation Temperature | 0 to 55°C [32 to 131°F] |
| Alarm Analysis Function | Supported |

10.4-inch W Model

GP-4501TW

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | |
|--------------------------------|----------------------------------------------------------------------------------------------|
| Model # | DC: PFXGP4501TADW |
| Coating Model | NO |
| Touch Panel Type | Analog Touch Panel |
| Display | 65,536 color TFT, LED Backlight, VGA 640x 480 |
| Memory | FLASH EPROM 16M byte (internal memory), SRAM 128K byte (backup memory) |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 |
| Operation Temperature | 0 to 50°C [32 to 122°F] |
| Alarm Analysis Function | Not Supported |

7.5-inch Standard Model

GP-4401T



| | |
|--------------------------------|----------------------------------------------------------------------------------------------|
| Model # | DC: PFXGP4401TAD |
| Coating Model | NO |
| Touch Panel Type | Analog Touch Panel |
| Display | 65,536 color TFT, 16-level Brightness Adjustment, LED Backlight, VGA 640x 480 |
| Memory | FLASH EPROM 32M byte (internal memory), SRAM 512K byte (backup memory) |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 |
| Operation Temperature | 0 to 55°C [32 to 131°F] |
| Alarm Analysis Function | Supported |

7.0-inch Wide W Model

GP-4401WW

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | |
|-------------------------|----------------------------------------------------------------------------------------------|
| Model # | DC: PFXGP4401WADW |
| Coating Model | NO |
| Touch Panel Type | Analog Touch Panel |
| Display | 65,536 color TFT, LED Backlight, WVGA 800x 480 |
| Memory | FLASH EPROM 16M byte (internal memory), SRAM 128K byte (backup memory) |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 |
| Operation Temperature | 0 to 50°C [32 to 122°F] |
| Alarm Analysis Function | Not Supported |

5.7-inch Standard Model

GP-4301T / GP4303T



| Model # | DC: PFXGP4301TAD | DC: PFXGP4301TADC | DC: PFXGP4303TAD |
|-------------------------|----------------------------------------------------------------------------------------------|--------------------------|-------------------------|
| Coating Model | NO | YES | - |
| Isolated | - | - | YES |
| Touch Panel Type | Analog Touch Panel | | |
| Display | 65,536 color TFT, 16-level Brightness Adjustment, LED Backlight, QVGA 320x 240 | | |
| Memory | FLASH EPROM 16M byte (internal memory), SRAM 512K byte (backup memory) | | |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1, SD card x 1 | | |
| Operation Temperature | 0 to 55°C [32 to 131°F] | | |
| Alarm Analysis Function | Supported | | |

5.7-inch W Model

GP-4301TW



| | | |
|--------------------------------|---------------------------------------------------------------------------------|---------------------------|
| Model # | DC: PFXGP4301TADW | DC: PFXGP4301TADWC |
| Coating Model | NO | YES |
| Touch Panel Type | Analog Touch Panel | |
| Display | 65,536 color TFT, LED Backlight, QVGA 320x 240 | |
| Memory | FLASH EPROM 8M byte (internal memory), SRAM 128K byte (backup memory) | |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1 | |
| Operation Temperature | 0 to 50°C [32 to 122°F] | |
| Alarm Analysis Function | Not Supported | |

3.5-inch Standard Model

GP-4201T / GP-4203T

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | | |
|--------------------------------|---------------------------------------------------------------------------|-------------------------|
| Model # | DC: PFXGP4201TAD | DC: PFXGP4203TAD |
| Coating Model | NO | - |
| Isolated | - | YES |
| Touch Panel Type | Analog Touch Panel | |
| Display | 65,536 color TFT, 16-level Brightness, LED Backlight, QVGA 320x 240 | |
| Memory | FLASH EPROM 16M byte (internal memory), SRAM 512K byte (backup memory) | |
| Interface | COM1 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1, Ethernet x 1 | |
| Operation Temperature | 0 to 50°C [32 to 122°F] | |
| Alarm Analysis Function | Supported | |

3.5-inch W Model

GP-4201TW

* Supported by GP-Pro EX Ver. 3.01 at the end of January, 2012.



| | |
|--------------------------------|--------------------------------------------------------------------------|
| Model # | DC: PFXGP4201TADW |
| Coating Model | NO |
| Touch Panel Type | Analog Touch Panel |
| Display | 65,536 color TFT, LED Backlight, QVGA 320x 240 |
| Memory | FLASH EPROM 8M byte (internal memory), SRAM 128K byte (backup memory) |
| Interface | COM1 x 1, COM2 x 1, USB Type A (2.0) x 1, USB mini B (2.0) x 1 |
| Operation Temperature | 0 to 50°C [32 to 122°F] |
| Alarm Analysis Function | Not Supported |