

SE HT cable ties with outside serrations for use at high temperatures

PA 6.6 black H.T.




SES®-QUICK

-40 to +110°C



• SE HT cable ties resistant to UV radiation- outside serrations

type	article number		dimensions length x width mm	maximum bundle Ø mm	tensile strength mini. (daN)
110/26 SE HT-C	0186 0606 010	100	110 x 2,6	24	8
125/47 SE HT-C	0186 0071 010	100	125 x 4,7	26	22
160/47 SE HT-C	0186 0076 010	100	160 x 4,7	38	22
185/47 SE HT-C	0186 0081 010	100	185 x 4,7	47	22
300/47 SE HT-C	0186 0087 010	100	300 x 4,7	80	22
370/47 SE HT-C	0186 0092 010	100	370 x 4,7	105	22
210/76 SE HT-C	0186 0674 010	100	210 x 7,6	52	53
300/76 SE HT-C	0186 0684 010	100	300 x 7,6	80	53
370/76 SE HT-C	0186 0688 010	100	370 x 7,6	103	53
175/90 SE HT-C	0186 0574 010	100	175 x 9	42	79
260/90 SE HT-C	0186 0577 010	100	260 x 9	69	79
360/90 SE HT-C	0186 0579 010	100	360 x 9	102	79
550/90 SE HT-C	0186 0083 010	100	550 x 8,9	155	79
780/90 SE HT-C	0186 0089 010	100	775 x 8,9	230	79

